



PC

IP67 Waterproof Counting Indicator

IP67



PC IP67 Waterproof Counting Indicator

Features:

- **Waterproof:** Stainless body with IP67 waterproof
- Up to 1/15,000 display resolution (Internal resolution 1/300,000)
- **Practical functions:** Accumulations (weight and quantity), Full range tare, Pre-tare, Auto-average unit weight, Kilogram (kg) and pound (lb) weighing modes, Auto backlight
- Auto calibration, Auto zero tracking, Low power and charging status indication
- **Selectable sampling speed:** speed 01-15
- **25 key design:** 10 / 20 / 50 / 100 pcs sampling keys included
- **Temperature calibration:** indoor / high / low temperature calibration point
- Built-in RS-232 interface with free format setting



Specifications:

- **Analog Input and A/D Conversion:** Input sensitivity 0.23 μ V/d (Min.)
- **Input Signal Range:** -1mV ~ +12mV
- **Input Zero Range:** -1mV ~ +5mV
- **Load Cell Excitation:** 5V DC $\pm$ 5% 100mA
- **Load Cell Drive Capacity:** up to 4 load cells at 350 Ω / load cell
- **Non-linearity:** 0.01% of full scale
- **A/D Resolution:** 500,000 counts (Max.)

Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Source	AC adaptor DC 9V or 6V / 4.5AH Rechargeable battery
Dimensions	256 x 170 mm (W x H)
Display	LCD, 5,5,6 Digits, 14 mm (Height), LED backlight

