

BARRIERAMTL7766PAC	<i>barrier supply</i>	RRP £ 153
BARRIERAMTL7761AC	<i>barrier signal</i>	RRP £ 153



PASSIVE FAIL-SAFE MTL7766PAC BARRIER (SUPPLY):

$-20^{\circ}\text{C} \leq T_a \leq +60^{\circ}\text{C}$; $P_o = 0.942\text{W}$; $C_o = 1.41 \mu\text{F}$; $L_o = 0.34 \text{mH}$; Each channel $U_o = 12\text{V}$;
 $I_o = 157\text{mA}$; $U_m = 250\text{V}$.

ATEX certified Ex II (1) G D [EEx ia] IIC BAS01ATEX7217

Dimensions: 105x12.6x82 mm.

Standard Omega/DIN rail mounting.

PASSIVE FAIL-SAFE MTL7761AC BARRIER (SIGNAL):

$-20^{\circ}\text{C} \leq T_a \leq +60^{\circ}\text{C}$; $P_o = 0.225\text{W}$; $C_o = 4.9 \mu\text{F}$; $L_o = 3.72 \text{mH}$; Each channel $U_o = 9\text{V}$;
 $I_o = 100\text{mA}$; $U_m = 250\text{V}$.

ATEX certified Ex II (1) G D [EEx ia] IIC BAS01ATEX7217

Dimensions: 105x12.6x82 mm.

Standard Omega/DIN rail mounting.