



P-EX2002

IP67 Waterproof
Multi-function Indicator

IP67



P-EX2002 IP67 Waterproof Multi-function Indicator

Features:

- **IP 67 waterproof:** moisture-proof, mist-proof, with IP67 waterproof and dustproof (Only the cables with $\phi 3\sim\phi 5.5\text{mm}$ caliber could be used or will affect the waterproof design)
- Stand alone batching mode or connect to PLC for external system control
- Built-in batching / dosing functions
- Manual / automatic discharge operation
- Set cycle times in a batch
- Totalise weight and number of cycles
- Key in the signal voltage value (mV/V) directly via the keyboard, no need to apply any weight to the bottomwork to calibrate the weigher
- Memorized load cell output voltage (mV/V) for future maintenance
- **Adjustable filter:** prevent vibration of environment
- RS232C bi-directional and current loop one way serial interface



Interfaces (Optional):

- OP-01 RS422/485/232 serial interface
- OP-03 16 Bit Analogue current/voltage output interface
(4 – 20 mA / 0 – 10V)
- OP-04 Control I/O (4 In / 4 Out) + Setpoint (BCD code)
- OP-05 Control I/O (8 In / 8 Out)

Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Source	AC 100V~240V, 50/60 Hz



P-EX2002 IP67 Waterproof Multi-function Indicator