couturier

EXCELL ®
Since ▶ 1979

ISO9001 CE RoHS WEEE compliant OIML

FD3-P / FDP3-P

Price Computing Scale

www.scalesearch.co.uk

FD3-P / FDP3-P
Price Computing Scale

Features:

■ FD3-P: Vendor side display at front and customer side display
■ FDP3-P: Vendor side display at front and one display on tower or double displays on tower
■ High speed 24bits AD
■ Faster display reading speed
■ Faster weighing stability and zero return
■ Zero key and Tare key react faster
■ Vendor and customer sides LCD displays with LED backlight
■ LCD display full tare (Weight-6 digits, Unit Price-6 digits, Total Price-6 digits)
■ Low power and charging status indication
■ Built-in rechargeable battery
■ Water channel designed underneath the platter to give a better protection against water running into the scale
■ Unique rubber ring design to prevent dust, dirt, cockroaches and water intrusion into the scale for better reliability and hygiene
■ Special power switch design to prevent moisture getting inside the scale for better performance stability and reliability

■ Special sunken power coil outlet design to prevent water running into the socket to improve safety and reliability
■ Easily adjusted leveling feet for stability and the scale

Approval Model:
■ 1/3,000 display resolution, multi-range

Options:

■ RS232 or serial printer output

530 mm

330 mm

300 mm

Specifications:

Model	Capacity	Division (multi-range)
FD3-P/FDP3-P-6	3 / 6 kg	1g / 2g
FD3-P / FDP3-P -15	6 /15 kg	2g / 5g
FD3-P / FDP3-P -30	15 / 30 kg	5g / 10g

Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F); **Approval Model:** -10°C ~ 40°C (14°F ~ 104°F)
Power Supply: AC 110/230V ±10%   6V/4AH Rechargeable Battery
Dimensions: FD3-P: 300 x 100 x 330 mm (W x H x D); FDP3-P: 300 x 530 x 330 mm (W x H x D)
Platter Size: 300 x 225 mm (W x D)
Display: LCD 6 digits, height 18mm; Pole display: height 14mm