

## PW

# IP67 Waterproof Weighing Indicator





#### PW IP67 Waterproof Weighing Indicator

#### Features:

- IP 67 waterproof: moisture-proof, mist-proof, with IP67 waterproof and dustproof (Only the cables with φ 3~ φ 5.5mm caliber could be used or will affect the waterproof design)
- Up to 1/15,000 display resolution (Internal 1/300,000)
- Large LCD display with LED backlight
- Kilogram (kg) and pound (lb) weighing modes
- Auto calibration; Full range tare; Auto-zero tracking; Simple counting; Gross/Net indication
- Hold function; Check mode Lo/Hi/OK
- Adjustable gravity value
- Low power indication and Auto power off
- Built-in RS-232 or Serial printer output



### Specifications:

- Analog Input and A/D Conversion: Input Sensitivity 0.3 
  µV/d (Min.)
- Input Signal Range: -1mV~+14mV
- Input Zero Range: -1mV~+5mV
- Load Cell Excitation: 5V DC ±5% 100mA
- Load Cell Drive Capacity: up to 4 load cells at 350 Ω load cell
- Non-linearity: 0.01% of full scale
- A/D Resolution: 500,000 counts (Max.)



**Operating Temperature** 

0°C ~ 40°C (32°F ~ 104°F)

**Power Source** 

AC adaptor DC 9V or 6V / 4.5Ah Rechargeable battery



