

TECHNICAL DATA



- ◆ External resolution... 1/3,000 EC version
- ◆ Display.....52mm LCD
- ◆ Keyboard.....7 keys mechanical switch
- ◆ Operating temp.....0°C ~ +40°C
- ◆ ADC.....sigma delta
- ◆ ADC update.....≤ 1/10 second
- ◆ Power.....AC adapter (9V/800mA)
Rechargeable battery (6V/4Ah)
Mains 240v or 110v

FEATURES

- ◆ Stainless steel waterproof design
- ◆ Easy to use - front panel configuration
- ◆ 52mm LCD, LED backlight
- ◆ application software includes: check weighing, parts counting, accumulation, animal weighing, keyboard lock
- ◆ Battery provides up to 90hours of continuous use.
- ◆ Low power indicator and Auto power off

SPECIFICATIONS

Display	52mm LCD with LED backlight
Housing	Stainless steel
IP Rating	Housing IP67 Load cell encapsulated IP67
Pan size	From 300 x 300mm to 700 x 500mm
Capacity	From 6kg to 300kg
Power Options:	AC adapter 9V/800mA with rechargeable battery, 6V/4Ah (EC approvable version) Mains powered 240v (110v option), with rechargeable battery 6v/4Ah (non trade version)
Keypad	7 keys