



ISO9001 CE



QW

Widescreen **IP68** Waterproof Weighing Indicator

QW

Widescreen *IP68* Waterproof Weighing Indicator



Features:

- Extra-large and wide LCD display (175 x 70mm) 6 digits with 55mm height
- LCD display with Cool White LED backlight
- RS-232 + RTC (Real Time Clock) interface
- Type 304 stainless steel housing
- IP 68: Mist-proof, waterproof and dustproof
- Up to 1/15,000 display resolution
- Unit switch key for Kilogram (kg) and pound (lb), etc.
- Full range tare, Pre-tare, Auto zero tracking, Sampling counting, Gross/Net Indication
- Hold function, Check mode Lo / Hi / OK, Auto average unit weight, and Animal scale function
- Low power indication and auto power off



J: 334 x 254mm



K: 322 x 242mm



- Waterproof pressure relief valve – for longer lifespan by preventing possible pressure build-up
- Wireless -or- RS-485
- Wireless for distance 10M or 100M available (SPP mode supported)
- Convenient foot switch for Zero, or Tare, or Print



Pressure Relief Valve



Specifications:

Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F)

Power Source: AC110V/220V+DC6V4.5AH rechargeable battery

Dimensions: 232 x 150 x 80mm (W x H x D)

Display: LCD, 6 Digits, 55 mm in height, Cool White LED backlight

Display Resolution: 1/15,000(Most Stable) -or- 1/30,000 -or- 1/60,000